



**BARCODE ELECTRONIC "OFF-LINE"
MERCHANT VALIDATION PRINTER
Model MV-2010**



*Model MV-2010 Bar Code Machine-
Readable Merchant Validation
Printer*

TRANSPORTABLE!

FEATURES:

- Easy front access ticket validating.*
- Safe, user-friendly operation*
- Print on the Fly** Barcode AutoRead*
- Rugged rust-resistant heavy duty industrial plastic construction.*
- Large back-lit LCD displays Date & Time, and optional programmable Message*
- Optional built-in LCD counters*
 - 1 Non-Resettable
 - 1 key Resettable
- Off-Line Operation capable*

Proudly made



in the U.S.A.

Sysparc, Inc.
16125 Cantlay St.
Van Nuys, Ca 91406

Phone: 818-902-1606
Fax: 818-902-1621
www.sysparc.com



I. Purpose:

The **Sysparc** Model MV-2010 Merchant Validation Printer is a revenue control device that provides a printed pre-programmed multiple-digit bar code machine-readable validation code on the face of the patron's entry ticket when inserted into the front of the printer.

This pre-programmed Merchant Validation number is then read by the Revenue Control exit device (fee computer, "Express Exit" Pay Station, Remote Parking (pay-on-foot) Pay Station, or Exit Verifier) where it is automatically read and used in the calculation of fee due from the parking patron.

II. Features & Functions:

- A. The **SysParc** Model MV-2010 Bar code Merchant Validation Printer is designed to issue a machine-readable validation code printed on the patron's entry ticket.
- B. The **SysParc** MV-2010 is activated by insertion of the patron's thermal stock entry ticket into the face of the validation printer.
- C. The Merchant Validation Printer issues one validation for each ticket inserted into the printer. In the event the patron's ticket has already received such a validation, this previous validation imprint will be detected, and no subsequent imprinting will occur.

III. Physical Description:

- A. The merchant Validation Printer's overall dimensions are 5.9" wide, by 6.8" deep, by 4.25" in height. It weighs 3 pounds.
- B. The electrical power requirement for the Merchant Validator is 115VAC at 60Hz, or 220VAC at 50Hz.
- C. The Merchant Validation Printer contains a micro-processor controlled mechanism which includes a date/time clock calendar. This microprocessor is programmed with its operating parameters.
- D. The Merchant Validation Printer is constructed of heavy duty industrial plastic,. The standard color is charcoal gray.



- E. Each ticket validation is printed at time of ticket insertion with the validation account number, and a sequential ticket validation number. This data is printed in both man-readable and barcode machine-readable format utilizing a non-contact thermal printer technology.

Sysparc, Inc.
16125 Cantlay St.
Van Nuys, Ca 91406

Phone: 818-902-1606
Fax: 818-902-1621
Website: www.sysparc.com

